

## NON-SPILL QUICK-RELEASE COUPLING SPT

Fuel filling line : filling  
 Fuel venting line  
 Fuel sampling  
 Fuel line safety break-away



### Non-spill

Flush-face design ensures no leakage when disconnecting.

### Safety Break-Away (SPT 05 & SPT 08)

Lanyard release feature ensures a safe fuel line break-away in a crash situation.

### Compact and Light Weight

Compact size, light weight combined with high strength aluminium construction provide optimum performance.

### Optimal Flow

Valve design ensures optimal flow with a minimum outside diameter.

### Rallye Raid Version (SPT 12)

Needed for gasoline refueling in the particularly dusty conditions of the Rallye Raid:

- tight aluminium cap to protect the plug
- rubber cap and rubber sleeve to protect the socket against dust and sand
- FIA approved.

### Technical characteristics

Type	SPT 05	SPT 08	SPT 12	SPT 12 RR
Nominal diameter (mm)	05	10	12	12
Max. working pressure* (bar)	12	12	12	12
Weight socket + plug (g)	41	80	260	295
Cross section (mm <sup>2</sup> )	19,6	50,2	113	113
Shut-off system	double	double	double	double
Option break-away	yes	yes	-	-

\* for other conditions of use (pressure, temperature, fluid...) please consult STÄUBLI

**Construction** High strength aluminium

**Seals** Fluorocarbon (FPM) | Fluorosilicon (FQM)

### Select your couplings:

	Motorbike	Car
safety break-away	SPT 05	SPT 08
fuel connection	SPT 05	SPT 08
fuel sampling	-	SPT 08
refuelling	-	SPT 12
rallye raid	-	SPT 12 RR